

### Description et characteristics techniques

- Prises Industrielles
- 16A to 125A
- 230V to 400V
- Protection IP44 to IP67
- Stabilité dimensionnelle : -25°C to +80°C

### References

| REF      | Description | AMPS | IP | Volts | PACK | CARTON |
|----------|-------------|------|----|-------|------|--------|
| 903131 A | 2P+T        | 16   | 44 | 230   | 1    | 10     |
| 903142 A | 3P +T       | 16   | 44 | 400   | 1    | 10     |
| 903152 A | 3P+N+T      | 16   | 44 | 400   | 1    | 10     |
| 903133 A | 2P+T        | 32   | 44 | 230   | 1    | 10     |
| 903144 A | 3P+T        | 32   | 44 | 400   | 1    | 10     |
| 903154 A | 3P+N+T      | 32   | 44 | 400   | 1    | 10     |

| REF      | Description | AMPS | IP | Volts | PACK | CARTON |
|----------|-------------|------|----|-------|------|--------|
| 903431 A | 2P+T        | 16   | 67 | 230   | 1    | 10     |
| 903442 A | 3P +T       | 16   | 67 | 400   | 1    | 10     |
| 903452 A | 3P+N+T      | 16   | 67 | 400   | 1    | 10     |
| 903433 A | 2P+T        | 32   | 44 | 230   | 1    | 10     |
| 903444 A | 3P +T       | 32   | 44 | 400   | 1    | 10     |
| 903454 A | 3P+N+T      | 32   | 44 | 400   | 1    | 10     |

| REF      | Description | AMPS | IP | Volts | PACK | CARTON |
|----------|-------------|------|----|-------|------|--------|
| 903435 A | 2P+T        | 63   | 67 | 230   | 1    | 10     |
| 903446 A | 3P +T       | 63   | 67 | 400   | 1    | 10     |
| 903456 A | 3P+N+T      | 63   | 67 | 400   | 1    | 10     |
| 903437 A | 2P+T        | 125  | 67 | 230   | 1    | 10     |
| 903448 A | 3P+T        | 125  | 67 | 400   | 1    | 10     |
| 903458 A | 3P+N+T      | 125  | 67 | 400   | 1    | 10     |



### Spécifications

- Directive 2014/35/UE. Low Voltage Electro technical Regulations
- Norme EN 60309-1, EN 60309-2
- Directive 2002/95/CE (RoHS)

### Characteristics Techniques

- Test do fil incandescent GWT 850°C (Glow Wire Temperature)
- Teste la boule: 125°C
- Matérielle sans halogène
- Système d'ouverture facile

