

Description et caracteristics techniques

- Prise pour fiches coudees
- 16A to 125A
- 230V to 400V
- Protection IP44 to IP67
- Stabilité dimensionnelle : -25°C to +80°C

References

| REF | Description | AMPS | IP | Volts | PACK | CARTON |
|---------|-------------|------|----|-------|------|--------|
| 931121A | 2P+T | 16 | 44 | 230 | 1 | 10 |
| 931142A | 3P+T | 16 | 44 | 400 | 1 | 10 |
| 931152A | 3P+N+T | 16 | 44 | 400 | 1 | 10 |
| 931123A | 2P+T | 32 | 44 | 230 | 1 | 10 |
| 931144A | 3P+T | 32 | 44 | 400 | 1 | 10 |
| 931154A | 3P+N+T | 32 | 44 | 400 | 1 | 10 |



| REF | Description | AMPS | IP | Volts | PACK | CARTON |
|---------|-------------|------|----|-------|------|--------|
| 931421A | 2P+T | 16 | 67 | 230 | 1 | 10 |
| 931442A | 3P+T | 16 | 67 | 400 | 1 | 10 |
| 931452A | 3P+N+T | 16 | 67 | 400 | 1 | 10 |
| 931423A | 2P+T | 32 | 67 | 230 | 1 | 10 |
| 931444A | 3P+T | 32 | 67 | 400 | 1 | 10 |
| 931454A | 3P+N+T | 32 | 67 | 400 | 1 | 10 |



| REF | Description | AMPS | IP | Volts | PACK | CARTON |
|---------|-------------|------|----|-------|------|--------|
| 931435A | 2P+T | 63 | 67 | 230 | 1 | 10 |
| 931446A | 3P+T | 63 | 67 | 400 | 1 | 10 |
| 931456A | 3P+N+T | 63 | 67 | 400 | 1 | 10 |
| 931437A | 2P+T | 125 | 67 | 230 | 1 | 10 |
| 931448A | 3P+T | 125 | 67 | 400 | 1 | 10 |
| 931458A | 3P+N+T | 125 | 67 | 400 | 1 | 10 |



| REF | Description | AMPS | IP | Volts | PACK | CARTON |
|--------|-------------|------|----|-------|------|--------|
| 931131 | 2P+T | 16 | 54 | 250 | 1 | 10 |
| 931431 | 2P+T | 16 | 67 | 250 | 1 | 10 |



| REF | Description | AMPS | IP | Volts | PACK | CARTON |
|---------|-------------|------|----|-------|------|--------|
| 931131F | 2P+T | 16 | 54 | 250 | 1 | 10 |

Spécifications

- Directive 2014/35/UE. Low Voltage Electro technical Regulations
- Norme EN 60309-1, EN 60309-2
- Directive 2002/95/CE (RoHS)

Characteristics Techniques

- Test do fil incandescent GWT 850°C
- Teste la boule: 125°C
- Matérielle sans halogène

