

Description et characteristics techniques

- Socle des fiches murales
- 16A to 125A
- 230V to 400V
- Protection IP44 to IP67
- Stabilité dimensionnelle : -25°C to +80°C

References

| RÉF | Combinaison | AMPS | IP | Volts | PACK | CARTON |
|--------|-------------|------|----|-------|------|--------|
| 935131 | 2P+T | 16 | 44 | 230 | 1 | 10 |
| 935142 | 3P+T | 16 | 44 | 400 | 1 | 10 |
| 935152 | 3P+N+T | 16 | 44 | 400 | 1 | 10 |
| 935133 | 2P+T | 32 | 44 | 230 | 1 | 10 |
| 935144 | 3P+T | 32 | 44 | 400 | 1 | 10 |
| 935154 | 3P+N+T | 32 | 44 | 400 | 1 | 10 |



| RÉF | Combinaison | AMPS | IP | Volts | PACK | CARTON |
|--------|-------------|------|----|-------|------|--------|
| 935446 | 3P+T | 63 | 67 | 400 | 1 | 10 |
| 935456 | 3P+N+T | 63 | 67 | 400 | 1 | 10 |



| RÉF | Combinaison | AMPS | IP | Volts | PACK | CARTON |
|--------|-------------|------|----|-------|------|--------|
| 935448 | 3P+T | 125 | 67 | 400 | 1 | 10 |
| 935458 | 3P+N+T | 125 | 67 | 400 | 1 | 10 |



Spécifications

- Directive 2014/35/UE. Low Voltage Electro technical Regulations
- Norm EN 60309-1, EN 60309-2
- Directive 2002/95/CE (RoHS)

Characteristics Techniques

- Test do fil incandescent GWT 850°C (Glow Wire Temperature)
- Teste la boule: 125°C
- Matérielle sans halogène

