

Description et characteristics techniques

- Socle des fiches murales
- 16A to 125A
- 230V to 400V
- Protection IP44 to IP67
- Stabilité dimensionnelle : -25°C to +80°C

References

RÉF	Combinaison	AMPS	IP	Volts	PACK	CARTON
935131	2P+T	16	44	230	1	10
935142	3P+T	16	44	400	1	10
935152	3P+N+T	16	44	400	1	10
935133	2P+T	32	44	230	1	10
935144	3P+T	32	44	400	1	10
935154	3P+N+T	32	44	400	1	10



RÉF	Combinaison	AMPS	IP	Volts	PACK	CARTON
935446	3P+T	63	67	400	1	10
935456	3P+N+T	63	67	400	1	10



RÉF	Combinaison	AMPS	IP	Volts	PACK	CARTON
935448	3P+T	125	67	400	1	10
935458	3P+N+T	125	67	400	1	10



Spécifications

- Directive 2014/35/UE. Low Voltage Electro technical Regulations
- Norm EN 60309-1, EN 60309-2
- Directive 2002/95/CE (RoHS)

Characteristics Techniques

- Test do fil incandescent GWT 850°C (Glow Wire Temperature)
- Teste la boule: 125°C
- Matérielle sans halogène

